



## 17" Touch LCD Monitor (DM-1700 Model)

- Using NEC Model LCD175VX
- Choice of Black or White Cabinet
- 3 Year Limited Warranty



### Product Specifications:

<b>Size/Type</b>	17 inch Diagonal/ Active Matrix LCD Display
<b>Touch Technology</b>	Resistive, Capacitive, or SAW
<b>Brightness</b>	(typical) 270 cd/m <sup>2</sup>
<b>Contents of Packaging</b>	User's Manual, Power cord, Setup Sheet & Driver CD
<b>Contrast Ratio</b>	(typical) 600:1
<b>Dimensions</b>	Net (with stand): 14.5 in. (W) x 14.1-16.1 in. (H) x 9.1 in. (D) 368 mm (W) x 358.5-408.5 mm (H) x 230 mm (D)  Net (without stand): 14.5 in. (W) x 12.6 in. (H) x 2.4 in. (D) 368 mm (W) x 320.5 mm (H) x 61 mm (D)
<b>Display Colors</b>	More than 16 million (Dependent upon display card used)
<b>Input Video Signal</b>	ANALOG: 0.7 Vp-p/75 Ohms
<b>Input</b>	DVI-D and VGA 15 pin D-sub
<b>Limited Warranty</b>	3 Years Parts and Labor including Backlight
<b>Operating Altitude</b>	3048m / 10,000 ft.
<b>Operating Humidity</b>	30-80%
<b>Operating Temperature</b>	5-35°C / 41-95°F
<b>Pixel Pitch</b>	0.264 mm
<b>Power Consumption</b>	On: 30W Power saving mode: 2W
<b>Resolutions Supported</b>	720 x 400 at 70 Hz - 1280 x 1024 @ 60 Hz



## 17" Touch LCD Monitor (DM-1700 Model)

### Product Specifications Continued:

<b>Storage Altitude</b>	12,192m / 40,000 ft.
<b>Storage Humidity</b>	10-85%
<b>Storage Temperature</b>	-10-60°C / 14-140°F
<b>Sync</b>	Separate Sync: TTL Level (positive/negative)
<b>Synchronization Range (Automatic)</b>	Horizontal: 31.5 kHz to 81 kHz (Analog/Digital) Vertical: 56 Hz to 76 Hz
<b>VESA Hole Configuration Spec.</b>	100mm x 100mm
<b>Viewing Angle</b>	(typical) 170° Vert. 176° Hor. (85U/85D/88L/88R) (CR>5)
<b>Voltage Rating</b>	100-240V @ 50/60Hz
<b>Weight</b>	Net: 10.6 lbs. / 4.8 kg Net (without stand): 8.4 lbs. / 3.8 kg
<b>Additional Features</b>	Thin-frame (bezel), tilt, No Touch Auto Adjust, cable management, touchscreen-compatible, NaViSet software, digital smoothing, digital controls, user (OSD) controls, Plug and Play (VESA DDC 1/2B), Accu-Color color control, DDC/CI, VESA DPMS power management, ISO 13406-2 Class II, Windows Vista Certified
<b>Response Time (typical)</b>	Rapid Response (5ms)

