



32" Large Touch LCD Monitor (LM-3200 Model)

- Using NEC Display Model LCD3215
- 3M DST Touch
- Optional Stand
- 3 Year Limited Warranty



Product Specifications:

Size/Type	32 inch Diagonal/ Active Matrix LCD Display
Touch Technology	DST Touch
Brightness	500 cd/m ²
Contents of Packaging	User's Manual, Power Cord, Wireless Remote, Batteries, Video Cable(s), Setup Sheet & Driver CD
Contrast Ratio	800:1
Dimensions	(WxHxD) Net (with stand) 31.1 x 21.2 x 9.7 in. Net (without stand) 31.1 x 18.8 x 5.2 in.
Input Signal	Video: ANALOG RGB 0.7 V _{p-p} / 75 Ohms Sync: Separate sync: TTL Level (Positive/Negative)
Input	DVI-D 24 pin (HDCP) Analog 15pin D-sub Analog BNC Composite (Shared RCA and BNC) or S-Video Component BNC (Y, Cb/Pb, Cr/Pr) Audio: Audio 1 (minijack) Audio 2 and 3 Stereo (RCA) Internal Speaker: None External Control: RS232C
Limited Warranty	3 Years Parts and Labor Including Backlight
Operating Humidity	20-80%
Operating Temperature	5-40° C/41-104° F
Storage Humidity	10-90%
Storage Temperature	-20-60° C/-4-140° F
Pixel Pitch	0.511mm
Power Consumption	(typical) On: 120W Power Savings Mode: <5W



32" Large Touch LCD Monitor (LM-3200 Model)

Product Specifications Continued:

Resolutions Supported	1366 x 768
Synchronization Range	Horizontal: 31.5-91.1 KHz (15.625,15.744 kHz) (Analog) 31.5-91.1 KHz (Digital) Vertical: 58-85 Hz Analog / 50-85 Hz Digital
VESA Hole Configuration Spec.	200 x 200mm (4 hole)
Viewing Angle	178° Vert. 178° Hor. (89U/89D/89L/89R) @ CR>10
Voltage Rating	AC 100-120V / AC 220-240V @ 50/60 Hz
Weight	(without stand) 28.9 lbs./13.1 kg
Additional Features	Power Management Plug and Play (DDC/CI DDC2B), PIP (Remote) Multi-level Zoom FullScan TileMatrix, TileComp Screen Saver Rapid Response Video Ready (no tuner) Infrared remote control included
Output	RGB: Daisy chain RGB3 Video: Daisy chain Video1 Audio: Daisy chain - Selected Audio in Control: RS232 for multiple monitor control Audio Amplifier: 7W x 7W

