



ONE WORLD
TOUCH
 TOUCH SCREEN SOLUTIONS

23" Performance Touch Monitor (PM-2323-43 Model)

- 20 Point Projected Capacitive Touch
- Tilt, Swivel, Pivot, Height Adjustable
- LED Backlit & Ambient Light Sensor
- 3 Year Limited Warranty



Product Specifications:

| | |
|--------------------------------------|---|
| Size/Type | 23 inch Diagonal/ IPS LCD Display, LED Backlight |
| Touch Technology | 20 Point Projected Capacitive |
| Brightness | 250 cd/m2 (Nits) |
| Contents of Packaging | User's Manual, Power Cord, VGA Video Cable, Setup Sheet & Driver CD |
| Contrast Ratio | 1000:1 |
| Resolution | 1920 x 1080 |
| Dimensions (W x H x D) | Net (with stand): 21.4 x 14.9-20.8 x 9 in./ 543.6 x 338-488 x 228mm Net (without stand): 21.4 x 12.7 x 2.9 in./ 543.6 x 322.6 x 74mm |
| Display Colors | 1.07 billion |
| Input | DVI-D, DisplayPort, HDMI & VGA 15 pin D-sub |
| Limited Warranty | 3 Years Parts and Labor including Backlight |
| Operating Altitude | 6562 ft./2000m |
| Operating Humidity | 30 to 80% |
| Operating Temperature | 41 to 95 F/ 5 to 35 C |
| Pixel Pitch | .270mm |
| Power Consumption | On: 29W, Power Savings Mode: .3W |
| Storage Altitude | 12,192m / 40,000 ft. |
| Storage Humidity | 10 to 85% |
| Storage Temperature | -10 to 60C/14 to 140F |
| Weight | (with stand) 22.5 lbs./10.2 kg (without stand) 15.4 lbs./ 7kg |
| VESA Hole Configuration Spec. | 100mm x 100mm |
| Viewing Angle | 178 Vert. 178 Hor. (89U/89D/89L/89R) (CR>10) |
| Voltage Rating | AC 100-120V / AC 220-240V |
| Response Time (typical) | 8ms |
| Additional Features | Ultra Thin-frame (bezel) No Touch Auto Adjust. Tilt, Pivot, VESA Mount, Cable Management, Carrying Handle, Swivel, Height-Adjustable Stand, 14 Bit 3D LUT, GammaComp, AmbiBright, Eco-Mode, Quick Release Stand, Ambix4 |

One World Touch, LLC reserves the right to change any of the information contained on this document without notice. We also reserve the right to discontinue, limit production or distribution of this or any other One World Touch, LLC product.