



# 24" LED Multi-Touch Monitor (LM-2432-43 Model)

- Using NEC Monitor P242W-BK
- 10 Point Projected Capacitive Touch
- Tilt, Swivel or Height Adjustable
- 3 Year Parts & Labor Warranty



## Product Specifications:

<b>Size/Type</b>	24.1 inch Diagonal/ IPS Panel with LED Backlighting
<b>Touch Technology</b>	10 Point Projected Capacitive with 60 GU Anti-Glare Coating
<b>Brightness</b>	350 cd/m2 (Nits)
<b>Resolution</b>	1920 x 1200
<b>Contents of Packaging</b>	User's Manual, Power Cord, Video Cable(s), Setup Driver CD
<b>Aspect Ratio</b>	16:10
<b>Contrast Ratio</b>	(typical) 1000:1
<b>Dimensions (W x H x D)</b>	Net (with stand): 21.9 x 14.9-20.8 x 9 in./ 556.3 x 378.5-528.3 x 228.6mm Net (without stand): 21.9 x 14.3 x 3.3in./ 556.3 x 363.2 x 83.8mm
<b>Display Colors</b>	More than 16.7 million
<b>Input</b>	DisplayPort, DVI-D, HDMI & VGA 15 pin D-sub
<b>Limited Warranty</b>	3 Years Parts and Labor including Backlight
<b>Operating Altitude</b>	5,000m / 16400 ft.
<b>Operating Humidity</b>	20 to 80%
<b>Operating Temperature</b>	5 to 35C/41 to 95F
<b>Pixel Pitch</b>	.270mm
<b>Power Consumption</b>	On: 29.5W, Power Savings Mode: .2W
<b>Storage Altitude</b>	12,192m / 40,000 ft.
<b>Storage Humidity</b>	10 to 85%
<b>Storage Temperature</b>	-10 to 60C/14 to 140F
<b>Synchronization Range</b>	Horizontal: 31.5-93.8/118.4 KHz Vertical:50.0-85.0 Hz
<b>VESA Hole Configuration Spec.</b>	100mm x 100mm
<b>Viewing Angle</b>	178 Vert. 178 Hor. (89U/89D/89L/89R) (CR>10)
<b>Voltage Rating</b>	AC 100-120V / AC 220-240V
<b>Weight</b>	(with stand) 22.5 lbs./10.2 kg (without stand) 15 lbs./ 6.8 kg
<b>Response Time (typical)</b>	8ms
<b>Additional Features</b>	ECO Mode, Ultra Thin-bezel, No Touch Auto Adjust, NaViSet software, Tilt, Swivel, Pivot, Height Adjustable, Quick Release Stand, Carrying Handle, Cable Management, OSD User Controls, 14 Bit 3D LUT, AmbiBright, CableComp, Carbon Footprint Meter, Rapid Response, XtraView+, HDCP, DDC/CI, Black Level Adjustment, GammaComp MD QA Software, SpectraView Software Ready