



65" Multi-Touch Display (LM-6526-39 Model)

- Using NEC Display Model V652
- Optical 6 Point Multi-Touch
- 1080p HD Resolution
- 3 Year Limited Warranty
- Internal 10W Speakers x 2



Product Specifications:

Size/Type	65 inch Diagonal/ Active Matrix LED Display
Touch Technology	Optical 6 Point Multi-Touch
Brightness	300cd/m2 (Typical), 450 cd/m2 (Max)
Contents of Packaging	User's Manual, AC Power cord, Wireless Remote, Batteries, 1.8m DVI-D cable, CD-ROM, Setup Sheet & Driver CD
Contrast Ratio	4000:1
Colors	more than 16.7 million (depending on video card used)
Dimensions	Net with stand: 60.6 x 37.2 x 20.2 in. / 1540.4 x 944.7 x 512mm Net without stand: 60.6 x 35.8 x 3.5in. / 1540.4 x 909.2 x 88.3mm
Input	DVI-D w/ HDCP, Analog D-Sub, Analog BNC, Composite RCA, S-Video, HDMI, DisplayPort, Component BNC, RS232, DDC/CI, Audio1 (minijack), Audio 2 and 3 stereo (RCA)
Limited Warranty	3 year including backlight
Operating Altitude	3000m/9842.5 ft.
Operating Humidity	20-80%
Operating Temperature	5-40 C/41-104 F
Pixel Pitch	0.74mm
Power Consumption	On: 185W , Power Savings Mode: <2W
Resolutions Supported	640x480, 800x600, 1024x768, 1280x768, 1360x768, 1280x1024 1600x1200 @ 60Hz (Compressed), 1920x1080 @ 60Hz (Recommended)
Storage Altitude	12,192m / 40000 ft.
Storage Humidity	10-90%
Storage Temperature	-20-60 C / -4-140 F
VESA Hole Configuration Spec.	400 x 400 mm (4 hole)
Viewing Angle	Up 89 / Down 89 / Left 89 / Right 89 (typ.)
Voltage Rating	AC 100-120V / AC 220-240V @ 50/60 Hz
Weight	Net with stand: 126 lbs., Net without stand: 115 lbs.
Additional Features	Power Management Plug and Play (DDC/CI DDC2B) PIP (Remote) Multi level Zoom, FullScan, 6 axis color CableComp TileMatrix TileComp Screen Saver Rapid Response, Video Ready (no tuner) Infrared remote control included