



## 19" Multi-Touch Monitor (DM-1937-36 Model)

- Desktop Monitor with VESA Mount
- 10 Point Projected Capacitive Touch
- Flat Front Touch Surface
- 3 Year Warranty



### Product Specifications:

|                                 |   |
|---------------------------------|---|
| <b>Size/Type</b>                | 19 inch Diagonal/ Active Matrix LCD Display   |
| <b>Touch Technology</b>         | Projected Capacitive Touch (10 Point Touch)   |
| <b>Brightness</b>               | 250 cd/m2 (typical) Nits with touchscreen   |
| <b>Resolution</b>               | 1280 x 1024   |
| <b>Contents of Packaging</b>    | User's Manual, Power Adaptor, Driver CD   |
| <b>Viewing Angle</b>            | 170 Degrees Horizontal, 160 Degrees Vertical  |
| <b>Contrast Ratio</b>           | 1000:1 (typical)  |
| <b>Dimensions with Stand</b>    | 16.76in. (W) x 15.71 in. (H) x 8.66 in. (D)<br>425.91mm (W) x 399.19 mm (H) x 220 mm (D)  |
| <b>Dimensions without Stand</b> | 16.76 in (W) x 13.80 in. (H) x 1.61 in. (D)<br>425.91 mm (W) x 350.65 mm (H) x 40.9 mm (D)  |
| <b>Display Colors</b>           | 262K (Dependent upon display card used)   |
| <b>Input Video Signal</b>       | VGA, HDMI, DVI  |
| <b>MTBF</b>                     | 50,000 (HR)   |
| <b>Stand Base</b>               | Tilt Down: 0, Tilt Up: +90 degrees  |
| <b>Limited Warranty</b>         | 3 Years Parts and Labor   |
| <b>Operating</b>                | Temperature: 0°C to 40°C / 32°-104° F<br>Humidity: 20% to 80%<br>Altitude: to 10,000 Feet<br>Storage Temperature: -20-60°C / -4-140°F<br>Storage Humidity: 10-90% (no condensation) |
| <b>Pixel Pitch</b>              | 0.294 mm  |
| <b>Power</b>                    | Universal Power Adapter<br>Input AC 100~240V, 50-60Hz<br>Output DC 12V/2A   |
| <b>Power Consumption</b>        | 18W   |
| <b>Certifications</b>           | CCC, CE, FCC  |