



24" Touch Monitors (LM-2400-44 Models)

- Using NEC Monitor P243W-BK
- Resistive, Capacitive or PCAP Touch
- Tilt, Swivel or Height Adjustable
- 3 Year Parts & Labor Warranty



Product Specifications:

Size/Type	24.1 inch Diagonal/ IPS Panel with LED Backlighting
Touch Technology	Resistive & Capacitive Single Touch, Projected Capacitive Multi-Touch (10 Pt)
Brightness	350 cd/m2 (Nits)
Resolution	1920 x 1200
Contents of Packaging	User's Manual, Power Cord, Video Cable(s), Setup Driver CD
Aspect Ratio	16:10
Contrast Ratio	(typical) 1000:1
Dimensions (W x H x D)	Net (with stand): 21.9 x 14.9-20.8 x 9.2 in./ 556.3 x 378.5-528.3 x 233mm Net (without stand): 21.9 x 14.2 x 2.3in./ 556.3 x 361.8 x 56.8mm
Display Colors	1.07 billion
Input	DisplayPort, DVI-D, HDMI & VGA 15 pin D-sub & USB B Ported (for Touch)
Limited Warranty	3 Years Parts and Labor including Backlight
Operating Altitude	5,000m / 16400 ft.
Operating Humidity	20 to 80%
Operating Temperature	5 to 35C/41 to 95F
Pixel Pitch	.270mm
Power Consumption	On: 25W, Power Savings Mode: .2W
Storage Altitude	12,192m / 40,000 ft.
Storage Humidity	10 to 85%
Storage Temperature	-10 to 60C/14 to 140F
Synchronization Range	Horizontal: 31.5-93.8/118.4 KHz Vertical:50.0-85.0 Hz
VESA Hole Configuration Spec.	100mm x 100mm
Viewing Angle	178 Vert. 178 Hor. (89U/89D/89L/89R) (CR>10)
Voltage Rating	AC 100-120V / AC 220-240V
Weight	(with stand) 19.5 lbs./8.84 kg (without stand) 13.4 lbs./ 6.07 kg
Response Time (typical)	8ms
Additional Features	ECO Mode, Ultra Thin-bezel, No Touch Auto Adjust, NaViSet software, Tilt, Swivel, Pivot, Height Adjustable, Quick Release Stand, Carrying Handle, Cable Management, OSD User Controls, 14 Bit 3D LUT, AmbiBright, CableComp, Carbon Footprint Meter, Rapid Response, XtraView+, HDCP, DDC/CI, Black Level Adjustment, GammaComp MD QA Software, SpectraView Software Ready