



**ONE WORLD**  
**TOUCH**  
TOUCH SCREEN SOLUTIONS

# 32" Multi-Touch Display (LM-3232-39F Model)

- Full 1080p Resolution (1920 x 1080)
- Projected Capacitive Multi-Touch
- OPS Expansion Slot for Internal PC
- Internal Speakers
- 3 Year Limited Warranty



## Product Specifications:

|                                      |   |
|--------------------------------------|---|
| <b>Size/Type</b>                     | 32 inch Diagonal/ S-IPS LCD Panel & LED Backlit   |
| <b>Touch Technology</b>              | Projected Capacitive 10 Point Multi-Touch   |
| <b>Resolution</b>                    | 1920 x 1080   |
| <b>Brightness</b>                    | 450 cd/m2   |
| <b>Audio</b>                         | Built-in speakers, & optional external speakers   |
| <b>Contents of Packaging</b>         | User's Manual, Power Cord, Wireless Remote, Batteries, DVI-D Cable Setup Sheet & Driver CD  |
| <b>Contrast Ratio</b>                | 1300:1  |
| <b>Dimensions</b>                    | Net (with stand) - (WxHxD)<br>29.5 x 19.6 x 9.4 in./750 x 497.1 x 240mm<br>Net (without stand)<br>29.5 x 17.5 x 2.4 in./750 x 444.5 x 60.8mm  |
| <b>Input Signal</b>                  | Video: ANALOG RGB Vp-p/75 Ohms Digital TMDS / DisplayPort<br>Sync: Separate sync: TTL Level (Positive/Negative)   |
| <b>Input</b>                         | <b>Digital</b> - HDMI, DVI-D, DisplayPort<br><b>Analog</b> - VGA 15-pin D-sub (shared S-Video, Video, Component, RGB)<br><b>Audio</b> - Stereo Mini-Jack, HDMI Audio, DisplayPort Audio<br><b>External Control</b> - RS-232C, Ethernet (RJ45), IR Remote                  |
| <b>Output</b>                        | <b>Audio</b> - Stereo Mini-Jack<br><b>Digital</b> - DVI-D   |
| <b>Limited Warranty</b>              | 3 Years Parts and Labor Including Backlight   |
| <b>Operating Humidity</b>            | 20-80%  |
| <b>Operating Temperature</b>         | 5-40° C/41-104° F   |
| <b>Storage Humidity</b>              | 10-90%  |
| <b>Storage Temperature</b>           | -20-60° C/-4-140° F   |
| <b>Pixels Pitch</b>                  | 0.36mm  |
| <b>Power Consumption</b>             | (typical) On: 48W / Power Savings Mode: <1W   |
| <b>Synchronization Range</b>         | Horizontal: Analog: 15.625 / 15.734 / 31.5 - 91.1 KHz, Digital: 31.5 - 91.1KHz<br>Vertical: 50-85 Hz Analog / 50-85 Hz Digital  |
| <b>VESA Hole Configuration Spec.</b> | 200 x 200mm (4 hole)  |
| <b>Viewing Angle</b>                 | 178° Vert. 178° Hor. (89U/89D/89L/89R)@ CR>10   |
| <b>Weight</b>                        | (with stand) 25.0 lbs./11.4 kg / (without stand) 23.8 lbs./10.8 kg  |
| <b>Additional Features</b>           | Ethernet Controllable, TileMatrix (10x10), TileComp, PIP/POP/Side by side picture, 6-axis color adjustment, 10-bit gamma, programmable zoom, scheduler, off-timer (countdown), screen saver, vacation switch, AutoBright, portrait mode capable, color temperature adjust |

One World Touch, LLC • 3003 Howard Lane, Austin TX 78728 • 512.341.9300 Main • [www.oneworldtouch.com](http://www.oneworldtouch.com)

One World Touch, LLC reserves the right to change any of the information contained on this document without notice. We also reserve the right to discontinue, limit production or distribution of this or any other One World Touch, LLC product.