



17" LED Touch Monitor (DM-1732-38B Model)

- Using NEC Model E172M-BK
- Projected Capacitive Multi-Touch
- Integrated Speakers
- 3 Year Limited Warranty



Product Specifications:

Size/Type	17 inch Diagonal/ LED Backlit LCD Display
Touch Technology	Projected Capacitive (PCAP) Multi-Touch 10 point touch capable
Brightness	(typical) 250 cd/m ²
Contents of Packaging	User's Manual, Power Cord, Video Cable(s), Setup Sheet & Driver CD
Contrast Ratio	(typical) 1000:1
Dimensions	Net (with stand) W x H x D: 14.5in x 14.1-16.1in x 9.1in/368mm x 358.5-408.5mm x 230mm Net (without stand) W x H x D: 14.5in x 12.6in x 2.4in/ 368mm x 320.5mm x 61mm
Display Colors	More than 16 million (Dependent upon display card used)
Input Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Input	DisplayPort, HDMI and VGA (15 pin D-sub)
Limited Warranty	3 Years Parts and Labor including Backlight
Operating Altitude	3048m / 10,000 ft.
Operating Humidity	30-80%
Operating Temperature	5-35°C / 41-95°F
Pixel Pitch	.264 mm
Power Consumption	On: 12W / Power saving mode: 0.15W
Resolutions Supported	1280 x 1024 Native Resolution
Storage Altitude	12,192m / 40,000 ft.
Storage Humidity	10-85%
Storage Temperature	-10-60°C / 14-140°F
Sync	Separate Sync: TTL Level (positive/negative)
Synchronization Range (Automatic)	Horizontal: 31.5 kHz to 81 kHz (Analog/Digital) Vertical: 56 Hz to 76 Hz
VESA Hole Configuration Spec.	100mm x 100mm
Viewing Angle	(typical) 160° Vert. 170° Hor. (80U/80D/85L/85R) (CR>5)
Voltage Rating	100-240V @ 50/60Hz
Weight	Net: 14.3 lbs. / 6.5 kg, Net (without stand): 8.8 lbs. / 4.0 kg
Additional Features	Tilt, No Touch Auto Adjust, cable management,, NaViSet software, digital smoothing, digital controls, user (OSD) controls, AccuColor color control, DDC/CI, VESA DPMS power management, ISO 13406-2 Class II
Certifications	CE, FCC Class B, RoHS, TCO, ES