



19" LED Multi-Touch Monitor (DM-1932-05C Model)

- Using NEC Model AS194Mi-BK
- Projected Capacitive Multi-Touch
- LED Backlit - Low Power Consumption
- 3 Year Limited Warranty



Product Specifications:

| | |
|--|--|
| Size/Type | 19 inch Diagonal/ IPS LCD Panel with LED Backlight |
| Touch Technology | Projected Capacitive (PCAP) Multi-Touch—10 Point Touch Capable |
| Brightness | 250 cd/m2 |
| Contents of Packaging | User's Manual, Power Cord, Video Cable(s), Setup Sheet & Driver CD |
| Contrast Ratio | 1000:1 |
| Aspect Ratio | 5:4 |
| Resolution | 1280 x 1024 |
| Pixels Per Inch | 87 |
| Power Consumption | On: 14W / Power saving mode: 0.3W |
| Viewing Angle | 178 Degree Vertical, 178 Degree Horizontal |
| Dimensions (W x H x D) | With Stand: 16.2 x 15.9 x 8.1 in. / 412.5 x 403.1 x 205.1 mm Without stand: 16.2 x 13.4 x 2.7 in. / 412.5 x 341.2 x 69 mm |
| Display Colors | More than 16.7 million |
| Input Video Signal | ANALOG: 0.7 Vp-p/75 Ohms |
| Input | DisplayPort, HDMI and VGA 15 pin D-sub |
| Limited Warranty | 3 Years Parts and Labor including Backlight |
| Operating Altitude | 2000m / 6,562 ft. |
| Operating Humidity | 20-80% |
| Operating Temperature | 5-35°C / 41-95°F |
| Storage Altitude | 12,192m / 40,000 ft. |
| Storage Humidity | 10-85% |
| Storage Temperature | -10-60°C / 14-140°F |
| Sync | Separate Sync: TTL Level (positive/negative) |
| Synchronization Range (Automatic) | Horizontal: 31.5 kHz to 81 kHz (Analog/Digital) Vertical: 56 Hz to 76 Hz |
| VESA Hole Configuration Spec. | 100mm x 100mm |
| Voltage Rating | 100-240V @ 50/60Hz |
| Weight | Net: 8.6 lbs. / 3.9 kg / Net (without stand): 7.5 lbs. / 3.4 kg |
| Additional Features | Tilt, No Touch Auto Adjust, cable management,, NaViSet software, digital smoothing, digital controls, user (OSD) controls, AccuColor color control, DDC/CI, VESA DPMS power management, ISO 13406-2 Class II |
| Response Time (typical) | Rapid Response (5ms) |